

NHIOICD-28 / NHIOICDCP-28

2" Iolite IC Air-Tight New Construction Housing

Source: 12W or 13W LED

800lm or 1000lm

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

New construction housing for use in insulated ceilings can be in direct contact with insulation. Air-tight construction provides energy savings by reducing the flow of air through the ceiling. Patented design allows for easy, tool-less removal of the driver.

SPECIFICATION

Housing: 0.040" Aluminum shallow housing can be installed in 1/2" ceiling thickness, an extension collar (NIO-2EXTC2) is available for ceiling thickness up to 2".

Patented Driver Assembly: Allows driver to slide out of housing without tools from the room side.

Air Flow Restriction: Meets requirements of Air-Tight (AT) <2CFM (cubic feet per minute) in accordance with ASTM-283 Air-Tight requirements.

Clearance: "IC" Insulated ceiling housings are direct contact rated. Not to be used in direct contact with spray foam insulation.

Bar Hangers: Two 13-3/4" to 24-1/2" adjustable bar hangers with captive nails are included on housing. Bar hangers are parallel to junction box, but can be repositioned 90° perpendicular to junction box if desired. "L"-shaped bar hanger foot to align to bottom of construction joist. A T-bar notch allows for easy installation in a suspended ceiling.

Junction Box: Pre-wired 25 cubic inch 0.064" thick galvanized steel, with seven 1/2" knockouts, four Romex® pryouts, and snap on covers. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Maximum of 8 no. 12 AWG through branch circuit conductors suitable for at least 90°C permitted in junction box. Junction box is accessible from the room side through housing opening.

| ELECTRICAL | LE3 | LE4 | LUPEQ |
|------------------------|-------------|---------------------|------------------|
| Input Voltage | 120V | 120-277V | 120/277V |
| Input Power | 13W | 12W | 13W |
| Power Factor | ≥0.90 | | |
| Dimming | Triac / ELV | Triac / ELV / 0-10V | Lutron EcoSystem |
| Operating Temp. | 40°C max. | | |

COMPATIBLE TRIMS & MONOPOINTS

| CATALOG NO. | DESCRIPTION |
|----------------------------|----------------------------------------|
| NIOB-2RC | 2" Round Adjustable Cone Regress |
| NIOB-2SC | 2" Square Adjustable Cone Regress |
| NIOB-2RG | 2" Round Adjustable Surface Gimbal |
| NIOB-2SG | 2" Square Adjustable Surface Gimbal |
| NIOB-2RND | 2" Round Deep Reflector |
| NIOB-2SND | 2" Square Deep Reflector |
| NIOB-2RPH | 2" Round Pinhole |
| NIOB-2RPHA | 2" Round Adjustable Pinhole |
| NIOB-2RSL | 2" Round Adjustable Slot Aperture |
| NIOB-2RNB | 2" Round Bullnose |
| NIOB-2SNB | 2" Square Bullnose |
| NIOB-2SND | 2" Square Reflector / Square Aperture |
| NIO-2RTLA | 2" Round Trimless Adjustable Reflector |
| NIO-2RTLND | 2" Round Trimless Reflector |
| NIOB-2RCY | 2" iPOINT Cylinder |
| NIOB-2RTC | 2" iPOINT Cone |



Emergency: Housing can be specified with connections for emergency battery installation. Requires access above the ceiling. Must specify battery with remote test switch separately, [NEPK-07LEDUNV](#). *Note: Emergency is not compatible with Chicago plenum housings.*

LABELS AND LISTINGS

- cULus Listed for Damp Locations (Wet Locations when used with compatible trim)
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- RoHS Compliant
- FCC compliant
- Patent #D824567S
- Meets or exceeds ASTM-283 Air-tight requirements



PRODUCT IMAGES AND DIMENSIONS



2" Iolite IC Air-Tight New Construction Housing - Compatible with NIOB-2, NIO-2 & NIOB-2

| Housing Type / Lumens | Driver / Dimming | Optional Emergency |
|---------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| NHIOICD-28 = IC Air-Tight 800lm or 1000lm | LE3 = 120V input; Triac / ELV dimming LE4 = 120-277V input; Triac / ELV / 0-10V dimming LUPEQ = 120/277V input; Lutron Hi-lume Premier 0.1% EcoSystem with Soft-On, Fade-to-Black (Consult factory) | /PEM = Pre-Wired for Remote Emergency |
| NHIOICDCP-28 = Chicago Plenum 800lm or 1000lm | LE3 = 120V input; Triac / ELV dimming LE4 = 120-277V input; Triac / ELV / 0-10V dimming LUPEQ = 120/277V input; Lutron Hi-lume Premier 0.1% EcoSystem with Soft-On, Fade-to-Black (Consult factory) | |

Optional Accessories

| Description |
|---------------------------------------------------------------|
| NEPK-07LEDUNV = Remote Emergency Battery w/Test Switch |
| NIO-2EXTC2 = Ceiling Extension Collar up to 2" |

Example: **NHIOICD-28LE3** = 2" Iolite IC Air-Tight New Construction Housing, 120V input; Triac / ELV dimming