

NL-3365

3" Adjustable Gimbal

FEATURES

Trim: Metal trim with adjustable ring can be adjusted up to 35°. Separate trim ring available in custom combination of ring finishes (consult factory).

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

LAMP

Low Voltage

Important: Do not use glass lens (provided) when already using lamp with glass cover
50W 12V MR16 (NL-301 Series; NLIC-301 Series)

LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



Type _____

Project _____

Catalog No. _____

Notes _____


Product Images and Dimensions



NL-3365B
Black Trim



NL-3365W
White Trim



3" Adjustable Gimbal

Catalog No. _____

NL-3365B = 3" Adjustable Gimbal, Black Finish

NL-3365W = 3" Adjustable Gimbal, White Finish

Compatible Housings

Low Voltage

Catalog No. _____

- NLIC-301AT/IEL** = 3" IC Air-Tight New Construction Housing / 50W max.
- NLIC-301QAT/20** = 3" IC Air-Tight New Construction Housing / 20W max.
- NLIC-301QAT/37** = 3" IC Air-Tight New Construction Housing / 37W max.
- NLIC-301QAT** = 3" IC Air-Tight New Construction Housing / 50W max.
- NL-301AT/IEL** = 3" Non-IC Air-Tight New Const. Housing / 50W max.
- NL-301QAT/20** = 3" Non-IC Air-Tight New Const. Housing / 20W max.
- NL-301QAT/37** = 3" Non-IC Air-Tight New Const. Housing / 37W max.
- NL-301QAT** = 3" Non-IC Air-Tight New Const. Housing / 50W max.

Example: **NL-3365B** = 3" Adjustable Gimbal, Black Finish